



260 mm x 480 mm x 174 mm KOYO NU3252
Single-row cylindrical roller bearings

Bearing No. NU3252

| | |
|-------------------------------|----------------|
| Size | 260x480x174 mm |
| Bore Diameter | 260 mm |
| Outer Diameter | 480 mm |
| Width | 174 mm |
| d | 260 mm |
| Fw | 320 mm |
| D | 480 mm |
| B | 174 mm |
| C | 174 mm |
| r min. | 5 mm |
| r1 min. | 5 mm |
| Weight | 139 Kg |
| Basic dynamic load rating (C) | 2140 kN |
| Basic static load rating (C0) | 3680 kN |
| (Grease) Lubrication Speed | 880 r/min |
| Bearing No. | NU3252 |
| r(min) | 5 |
| r1(min) | 5 |
| Cr | 2680 |
| C0r | 3680 |
| Cu | 373 |
| Grease lub. | 880 |
| Oil lub. | 1300 |
| Ew | - |
| d1 | - |

NU3252 Bearing 2D drawings and 3D CAD models



Shandong Weisen Bearing Co., Ltd

| | |
|------------------|-----|
| B1 | - |
| B2 | - |
| da(min) | - |
| db(min) | 280 |
| db(max) | 318 |
| dc(min) | - |
| dd(min) | - |
| Da(max) | 460 |
| Db(max) | - |
| Db(min) | - |
| ra(max) | 4 |
| rb(max) | 4 |
| (Refer.)Mass(kg) | 139 |